

		AN 26W	N 40	PD 50	WA 50
Type of additive		dispersant	dispersant	Wax emulsion	dispersant
Solid content	[%]	30	40	50	50
pH		9,0 – 10,0	7,5 – 8,5	9,0 ±1	6,0 – 7,0
viscosity ¹⁾	[mPas]	300 - 1500	250 - 650	100 - 400	100 - 300
density	[g/cm ³]	1,05 ±0,02	1,28 ±0,02	0,98 ±0,02	1,00 ±0,02

Field of application					
Solvent-free systems		**	**	**	
Paints free of preservatives		**	**	**	
Interior paints		**	**	**	
Exterior paints		**	**		
High and satin-gloss paints			**		
Tinting paints			**		**
Silicon paints and plasters					**
Silicate paints and plasters			**		
Synthetic resin plasters					
Colored stone plasters		**	**		
Roof coatings			**		
Floor coatings		**	**		
Water-based varnishes			**		
Adhesives		**	**		
Wood coatings		**	**		

¹⁾ Brookfield viscosimeter 20 RPM

* especially suitable
** conditionally suitable

IMPARAT Farbwerk
Iversen & Mähl GmbH & Co. KG
IMPARAT Polymer
21509 Glinde / Hamburg
Tel. 040/727708-341 Fax 040/727708-349
www.imparat.de

This data corresponds to our present state of knowledge. It results from tests in our research laboratories and is intended to provide information on our products and their application possibilities. This does not represent a guarantee or bind assurance of certain characteristics of products or their suitability for certain applications. Any existing patent rights must be observed. Our "General Terms of Business" apply.
21.07.2022